

SMARTMOUNT ADVANCED

Part Number: GS-3-SMA



SMARTMOUNT Advanced uses a traditional camera for advanced detection applications 200 to 400 feet from the camera.

SPECIFICATIONS

CAMERA

Connectivity: Single CAT5e Cable
Dimensions: 15.9" x 6.4" x 5.6" (40.4 x 16.25 x 14.2 cm)
Weight: 6.8 lbs (3 kg)
Power: Power over Ethernet (PoE)
Cable Length: 5' (1.52 m)
Consumption: 5W nominal
15W with active camera heaters
Environmental: -29°F to 165°F (-34°C to 74°C)
0 to 95% non-condensing
Material: Aluminum
Image Format: MJPEG color

POLE ASSEMBLY

Dimensions: 5' extension (1.52 m)
Weight: 5.8 lbs (2.6 kg)
(4.5 lbs pipe, 1.3 lbs bracket)
Material: 1.5" (3.81 cm) schedule 40 aluminum pipe - 6063-T52

JUNCTION BOX

Connectivity: M12 (to Camera)
RJ-45 CAT5e (to Processor)
Dimensions: 9.5" x 3.5" x 3.5" (24.13 x 8.89 x 8.89 cm)
Weight: 0.7 lbs (0.32 kg)
ABA Material: Polycarbonate/ASA blend, UV Stabilized
Environmental: -29°F to 165°F (-34°C to 74°C)
0 to 95% non-condensing
Rated: IP67

MOUNTING KIT

Weight: 2.75 lbs (1.25 kg)
(2 lbs camera mounting hardware and screws,
0.75 lbs cable)
Wind Testing: Wind Tunnel Tested: >150 mph